

# SOP-CABLE Br M8 TIRAF 50/70

77909100



M8 bronze bracket with screw rings, for 50 and 70 mm<sup>2</sup> cable.

Scan this QR code and see the full range



[Link to the product page](#)

Technical Data	Value	Units
<b>Commercial data</b>		
Code	77909100	
Part Number	SOP-CABLE Br M8 TIRAF 50/70	
Status	Available	
EAN	8435297812777	
Tariff code (HS)	74199990	
<b>Dimensions</b>		
Product height	73,4	[mm]
Product width	36	[mm]
Product length	20	[mm]
Product weight	65	[gr]
Packaging unit	1	
<b>General data</b>		
Product standards	EN 62561-4:2011	
Certifications	CE	
<b>Technical features</b>		
Down-conductor system	Cable conductor	
Max. diameter of cable	Diámetro máx.cable	10 [mm]
Min. diameter of cable	Diámetro mín cable	8 [mm]
Material	Brass	
Connector material	Copper	
Screw thread	M8	

Certifications	Value	Units
Certifications	CE	

Address



**Barcelona**

**Cirprotec, S.L.U.**

C/ Lepanto, 49

08223 - Terrassa (Barcelona)

Tel. +34 937 331 684

Fax. +34 93 733 27 64

[www.cirprotec.com](http://www.cirprotec.com)

Copyright © Cirprotec, S.L.

[Legal Notice](#)

# SOP-COND D-8/10 TF MET FeCG

77600030

Support in galvanized steel for cable 8-10mm with dowel for metallic structure.

Scan this QR code and see  
the full range



[Link to the product page](#)

Technical Data	Value	Units
<b>Commercial data</b>		
Code	77600030	
Part Number	SOP-COND D-8/10 TF MET FeCG	
Status	Available	
EAN	8435297866299	
Tariff code (HS)	74199990	
<b>Dimensions</b>		
Product height	28	[mm]
Product width	42	[mm]
Product length	20	[mm]
Packaging unit	1	
<b>General data</b>		
Product standards	EN 62561-4:2011	
Certifications	CE	
<b>Technical features</b>		
Down-conductor system	Cable conductor	
Max. diameter of cable	Diámetro máx.cable	10 [mm]
Min. diameter of cable	Diámetro mín cable	8 [mm]
Material	Stainless steel	
Connector material	Stainless steel	
Screw thread	M6	

[Link to the product page](#)

Certifications	Value	Units
Certifications	CE	

Address



**Barcelona**

**Cirprotec, S.L.U.**

C/ Lepanto, 49

08223 - Terrassa (Barcelona)

Tel. +34 937 331 684

Fax. +34 93 733 27 64

[www.cirprotec.com](http://www.cirprotec.com)

Copyright © Cirprotec, S.L.

[Legal Notice](#)

# SOP-COND PLETINA Cu 30MM TACO

7760001182



Down conductor copper support for 30mm tape with M8 dowel

Scan this QR code and see the full range



[Link to the product page](#)

Technical Data	Value	Units
----------------	-------	-------

## Commercial data

Code	7760001182	
Part Number	SOP-COND PLETINA Cu 30MM TACO	
Status	Available	
EAN	8435297873082	
Tariff code (HS)	74199990	

## Dimensions

Product height	73,4	[mm]
Product width	53	[mm]
Product length	20	[mm]
Packaging unit	1	

## General data

Product standards	EN 62561-4:2011	
Certifications	CE	

## Technical features

Down-conductor system	Flat tape	
Max. flat tape width	30	[mm]
Min. flat tape width	25	[mm]
Max. flat tape thickness	3	[mm]
Min. flat tape thickness	2	[mm]
Material	Brass	
Connector material	Copper	
Screw thread	M8	

Certifications	Value	Units
Certifications	CE	

Address



**Barcelona**

**Cirprotec, S.L.U.**

C/ Lepanto, 49

08223 - Terrassa (Barcelona)

Tel. +34 937 331 684

Fax. +34 93 733 27 64

[www.cirprotec.com](http://www.cirprotec.com)

Copyright © Cirprotec, S.L.

[Legal Notice](#)

# SOP-COND TF NYLON D8MM

776001155

## Nylon support for down conductor cable 8mm with dowel



Scan this QR code and see the full range



[Link to the product page](#)

Technical Data	Value	Units
<b>Commercial data</b>		
Code	776001155	
Part Number	SOP-COND TF NYLON D8MM	
Status	Available	
EAN	8435297840831	
Tariff code (HS)	74199990	
<b>Dimensions</b>		
Product height	60	[mm]
Product width	22	[mm]
Product length	22	[mm]
Packaging unit	1	
<b>General data</b>		
Product standards	EN 62561-4:2011	
Certifications	CE	
<b>Technical features</b>		
Down-conductor system	Cable conductor	
Max. diameter of cable	Diámetro máx.cable	8 [mm]
Min. diameter of cable	Diámetro mín cable	8 [mm]
Material	Nylon	
Connector material	Nylon	
Screw thread	M8	

Certifications	Value	Units
Certifications	CE	

Address



**Barcelona**

**Cirprotec, S.L.U.**

C/ Lepanto, 49

08223 - Terrassa (Barcelona)

Tel. +34 937 331 684

Fax. +34 93 733 27 64

[www.cirprotec.com](http://www.cirprotec.com)



# METALLIC COLLAR PLETINA

776110254

Metallic collar for fastening 30mm tape down conductor to pipe 80-150mm diameter.



Indicative product image

Technical Data	Value	Units
<b>Commercial data</b>		
Code	776110254	
Part Number	METALLIC COLLAR PLETINA	
<b>Dimensions</b>		
Packaging unit	1	
<b>General data</b>		
Product standards	EN 62561-4:2011	
Certifications	CE	
<b>Technical features</b>		
Max. flat tape width	30	[mm]
Min. flat tape width	25	[mm]
Max. flat tape thickness	3	[mm]
Min. flat tape thickness	2	[mm]
Max. mast diameter	150	[mm]
Min. mast diameter	80	[mm]
Connector material	Stainless steel	
Housing material	Stainless steel	
Screw thread	M8	

# SOP-COND PL30 TF MET FeCG

77600035

Support in galvanized steel for pletina 30mm with dowel for metallic structure.



Indicative product image

Technical Data	Value	Units
<b>Commercial data</b>		
Code	77600035	
Part Number	SOP-COND PL30 TF MET FeCG	
Status	Available	
<b>Dimensions</b>		
Product height	31	[mm]
Product width	54	[mm]
Product length	20	[mm]
Packaging unit	1	
<b>General data</b>		
Product standards	EN 62561-4:2011	
Certifications	CE	
<b>Technical features</b>		
Max. flat tape width	30	[mm]
Min. flat tape width	25	[mm]
Max. flat tape thickness	3	[mm]
Min. flat tape thickness	2	[mm]
Material	Stainless steel	
Connector material	Stainless steel	
Screw thread	M6	

# CONEC-KS 1S FeCG / AI

776001360

**KS connector for 1 support.**

Scan this QR code and see  
the full range



[Link to the product page](#)

Technical Data	Value	Units
<b>Commercial data</b>		
Code	776001360	
Part Number	CONEC-KS 1S FeCG / AI	
Status	Available	
EAN	8435297808206	
Tariff code (HS)	8536.30.90	
<b>Dimensions</b>		
Product weight	52	[gr]
<b>General data</b>		
Certifications	CE	
<b>Technical features</b>		
Down-conductor system	Cable conductor	
Diameter	6-10	[mm]
Max. diameter of cable	Diámetro máx.cable	8 [mm]
Min. diameter of cable	Diámetro mín cable	10 [mm]
Material	Steel galvanized - aluminum	

Certifications	Value	Units
Certifications	CE	

Address



**Barcelona**

**Cirprotec, S.L.U.**

C/ Lepanto, 49

08223 - Terrassa (Barcelona)

Tel. +34 937 331 684

Fax. +34 93 733 27 64

[www.cirprotec.com](http://www.cirprotec.com)

# GRAPA LIGERA PLETINA

77934202



Galvanized steel staples for fastening flat strip conductors.

Scan this QR code and see the full range



[Link to the product page](#)

Technical Data	Value	Units
----------------	-------	-------

## Commercial data

Code	77934202	
Part Number	GRAPA LIGERA PLETINA	
Status	Available	
EAN	8435297849728	
Tariff code (HS)	7326.90.98	

## Dimensions

Product height	5	[mm]
Product width	2	[mm]
Product length	8	[mm]
Product weight	25	[gr]
Packaging unit	1	

## General data

Product standards	EN 62561-4:2011	
-------------------	-----------------	--

## Technical features

Down-conductor system	Flat tape	
Max. flat tape width	30	[mm]
Min. flat tape width	25	[mm]
Max. flat tape thickness	3	[mm]
Min. flat tape thickness	2	[mm]
Material	Galvanized steel	

## Address



**Barcelona**

**Cirprotec, S.L.U.**

C/ Lepanto, 49

08223 - Terrassa (Barcelona)

Tel. +34 937 331 684

Fax. +34 93 733 27 64

[www.cirprotec.com](http://www.cirprotec.com)

Copyright © Cirprotec, S.L.

[Legal Notice](#)

# METALLIC COLLAR

776110251

**Metallic collar for fastening 8mm cable down conductor to pipe 80-150mm diameter.**



Scan this QR code and see the full range



[Link to the product page](#)

Technical Data	Value	Units
<b>Commercial data</b>		
Code	776110251	
Part Number	METALLIC COLLAR	
Status	Available	
EAN	8435297852766	
Tariff code (HS)	8536.30.90	
<b>Dimensions</b>		
Product height	15,5	[mm]
Product width	150	[mm]
Product length	150	[mm]
Packaging unit	1	
<b>General data</b>		
Product standards	EN 62561-4:2011	
Certifications	CE	
<b>Technical features</b>		
Down-conductor system	Cable conductor	
Max. mast diameter	Ø máx mástil	150 [mm]
Min. mast diameter		80 [mm]
Max. diameter of cable	Diámetro máx.cable	8 [mm]
Min. diameter of cable	Diámetro mín cable	8 [mm]
Material	Stainless steel	
Connector material	Stainless steel	
Housing material	Stainless steel	
Screw thread	M8	

Certifications	Value	Units
Certifications	CE	

Address



**Barcelona**

**Cirprotec, S.L.U.**

C/ Lepanto, 49

08223 - Terrassa (Barcelona)

Tel. +34 937 331 684

Fax. +34 93 733 27 64

[www.cirprotec.com](http://www.cirprotec.com)