

G-CHECK

Power monitoring for power lines
Grounding system monitor



General Data




PART NUMBERS		
XXX	120	230
G-CHECK XXXV	77706550	77706500

TECHNICAL FEATURES		
G-CHECK XXXV	120	230
Nominal voltage AC 50-60 Hz - Un [V]	120	230
Maximum output power (to neutral) - Iout [VA]	70	
Actuation value for alarm - Ra	Adjustable	
Max. measurement value [Ohm]	500	
Monitoring method	Grounding loop monitoring	

MECHANICAL AND ENVIRONMENTAL FEATURES		
G-CHECK XXXV	120	230
Temperature range [°C]	-20 ... 60	
Indication System Type	Visual Indicator	
Enclosure - IP	IP20	
Solid conductor cross section	6...35 mm ²	
Stranded conductor cross section	6...25 mm ²	

DIMENSIONS AND WEIGHT		
G-CHECK XXXV	120	230
Net Weight [kg]	0.18	
Gross weight [kg]	0.2	
Packaging dimensions (H x W x L) [mm]	105 × 45 × 80	



DATASHEET

This document is subject to change at any time without notice www.cirprotec.com | Lepanto 49 · 08223 Terrassa, Barcelona Spain © 2024 Cirprotec SLU | All rights reserved

cirprotec